





Frese ALPHA Cartridges · Quick Guide

Combining housings and cartridges



		Frese ALPHA Cartridge Type 10, 11, 20 -20°C to +120 °C	Frese ALPHA Cartridge Type 30, 40 -20°C to +120 °C	Frese ALPHA Cartridge Type 50, 60 -20°C to +120 °C	Frese ALPHA Cool Cartridge -20°C to +80°C
Valves	Thread	Flow l/h	Flow l/h		
Frese ALPHA DN15-DN25	Female/Female	25-2,448			
	Fixed end female/ union	25-2,448			
Frese EVA DN15-DN25	For unions with actuator	25-2,448			
Frese EVA Basic DN15	For couplings with actuator	25-2,448			
Frese ALPHA DN25L-DN50	Female/Female		677-11,355		
Frese ALPHA DN25L-DN40	Fixed end female/ union		677-11,355		
Wafers				Flow l/h	Flow l/h
Frese ALPHA DN50				3,820-45,000	3,404-47,000
Frese ALPHA DN65				3,820-45,000	3,404-47,000
Frese ALPHA DN80				3,820-45,000	3,404-47,000
Frese ALPHA DN100				3,820-90,000	3,404-95,000
Frese ALPHA DN125				3,820-135,000	3,404-143,000
Frese ALPHA DN150				3,820-180,000	3,404-190,000
Frese ALPHA DN200				3,820-315,000	3,404-333,000
Frese ALPHA DN250				3,820-540,000	3,404-572,000
Frese ALPHA DN300				3,820-675,000	3,404-715,000
Frese ALPHA DN350				3,820-855,000	3,404-906,000
Frese ALPHA DN400				3,820-1,170,000	3,404-1,239,000
Frese ALPHA DN450				3,820-1,485,000	3,404-1,573,000
Frese ALPHA DN500				3,820-1,800,000	3,404-1,907,000
Frese ALPHA DN600				3,820-2,520,000	3,404-2,670,000
Frese ALPHA DN800				3,820-3,825,000	3,404-4,053,000

Frese A/S assumes no responsibility for errors, if any, in catalogues, brochures, and other printed matter. Frese A/S reserves the right to modify its products without prior notice, including already ordered products, if this does not alter existing specifications. All registered trademarks in this material are the property of Frese A/S. All rights reserved.

Frese A/S
Sorøvej 8
DK- 4200 Slagelse
Tel: +45 58 56 00 00
info@frese.dk